



Note: Load charts are provided as a guide only, to provide indicative capacities, they are extracts from the full versions.

UNIT:x1000kg

Outriggers fully extended 7.0m																				
B \ A	11.0m		15.0m		19.0m		27.0m		35.0m		39.0m		43.0m							
	C		C		C		C		C		C		C							
3.0	70	60.0	76	40.8	79	32.0	79	22.0												
3.5	67	47.5	74	40.8	78	32.0	78	22.0												
4.0	64	42.4	72	40.8	76	32.0	76	22.0	81	22.0	81	17.0								
4.5	61	38.1	70	37.8	75	32.0	75	22.0	80	22.0	80	17.0								
5.0	58	34.5	68	34.2	73	32.0	73	22.0	79	22.0	79	17.0								
5.5	55	31.4	66	31.1	72	30.9	71	21.4	78	21.3	78	17.0								
6.0	51	28.7	63	28.4	70	27.4	70	20.6	77	20.7	77	17.0	80	14.0	81	12.0				
6.5	47	26.4	61	26.1	68	24.0	68	19.8	76	20.0	76	16.3	80	14.0	80	12.0				
7.0	43	24.4	59	23.5	67	21.1	66	19.1	75	19.5	75	15.4	79	14.0	79	11.9	80	10.0		
7.5	39	22.7	57	20.9	65	18.8	65	18.5	74	18.8	73	14.6	78	13.5	78	11.5	80	10.0		
8.0	34	20.0	54	18.7	63	16.9	63	17.9	72	17.1	72	13.9	77	13.0	77	11.1	79	10.0	80	8.5
9.0	20	15.7	49	15.0	60	13.9	60	16.8	70	14.3	70	12.6	76	12.1	76	10.3	78	10.0	79	8.5
10.0			43	12.0	56	11.6	56	14.7	68	12.2	68	11.6	74	11.7	74	9.7	76	9.7	78	8.5
11.0			36	9.8	52	9.5	52	12.4	65	10.5	65	10.7	72	10.2	72	9.0	75	9.2	77	8.5
12.0			28	8.2	47	7.9	48	10.6	63	9.2	63	9.9	70	9.0	71	8.4	73	8.7	76	8.1
14.0					37	5.5	38	7.9	58	6.9	58	8.3	67	7.1	67	7.3	70	7.5	73	6.9
16.0					24	3.8	25	6.2	52	5.2	52	6.5	63	5.6	63	6.4	67	6.1	70	5.5
18.0									46	3.9	46	5.2	59	4.4	59	5.4	63	5.0	66	4.4
20.0									39	3.0	40	4.2	55	3.5	55	4.4	60	4.0	63	3.6
22.0									31	2.2	32	3.5	50	2.7	51	3.6	56	3.2	60	2.9
24.0									20	1.6	22	2.9	46	2.1	46	3.0	52	2.6	57	2.3
26.0													41	1.6	41	2.5	48	2.1	53	1.8
28.0													35	1.2	35	2.1	43	1.7	50	1.4
30.0													28	0.8	28	1.7	39	1.3	46	1.0
32.0													18	0.5	18	1.4	33	1.0	42	0.7
34.0																	26	0.8	37	0.5
36.0																	17	0.6		
D								0°					18°		0°		17°		37°	